



VISION® Datasheet

124718 V21-SMAS Satellite Masthead Amplifier Supply

Designed to be used in hybrid legacy IRS systems to power a masthead amplifier where there is no power available.

- Satellite Input Voltage 13~18VDC
- Extracts voltage from 18VDC HH
- Masthead Powering 12VDC regulated 100mA
- 18mm pitch between connectors
- Short circuit Protection
- Bi-Coloured LED, Green "ON", Red SC Fault
- Insertion Loss <1dB Satellite / Terrestrial
- IP53 Weather Proof Masthead housing with wide tie wrap



Model	V85-SMAS 124718	
Input Frequency	88—790MHz / 11.70 – 12.75GHz	
Output Frequency	88—790MHz / 11.70 – 12.75GHz	
Isolation Terr / High Band	>30dB	
Insertion Loss	<1dB	
Operating Voltage	13-18VDC	
Max. Current regulated	100mA@12VDC	
Pitch between Connectors	18mm	
Weather poof Housing	Yes	
Operating Temperature	-30 ⁰ C to +70 ⁰ C	
Dimension HxWxD (mm) / Weight g	115.4 x 115.55 x 48mm	219g
Box Dimensions HxWxD (mm) / Weight g	62.5 x 12.2 x 144.5mm	36g

©2020 Vision Products (Europe) Ltd. Vision and the vision eye device are registered trademarks of Vision Products (Europe) Ltd. In the interests of continued product improvement and development we reserve the right to change specifications, design and dimensions without prior notice. Details correct at date of publication E&OE

Vision Products (Europe) Ltd, Vision House, 24 Faraday Court, Wellingborough, Northamptonshire NN8 6XY
Tel: 01933 677 220 Email: technical@vision-products.co.uk Company Reg No: 5044512

www.vision-products.co.uk

